## PETROL HIGH FLOW HYDROSTATIC PIPE BARRET TESTER

SKU: 210 APS41-R210E BASE

### Powerease 7 hp E Start Engine Comet Italian Pump 568 psi @ 41 L/min

#### **Features**

- Our range of hydro testers are designed for the contractor who needs a reliable, high quality pipe tester.
- Supplied standard with:
  - o Comet Italian Diaphragm pump
  - o Enclosed gear box
  - Double pressure gauge and lock off ball valve system
  - o Your choice of frame
  - o Inlet water filter

#### • Applications include:

- Pipeline pressure testing
- Leak detection
- o Hydrostatic testing of pressure vessels

#### • Optional equipment:

- NATA certified pressure gaugesÿ
- Skid Mount Units
- o 600 Litre poly water tank on skid mount units
- 2000 psi to 7250 psi (140-500Bar) units built to your needs

#### • Dual Valve System:

- All hydrostatic pressure test units are fitted with a dual valve system. This isolates the pressure pump from the item under test when the test pressure is reached.
- When isolated the test piece is monitored during the test period on the second pressure gauge for any pressure drop, which would indicate a leak.

#### **Specifications**

• Maximum Pressure: 568 Psi (40 Bar)

Maximum Flow: 41 L/min
Engine - Brand: Powerease
Engine - Model: R210
Engine - Power: 7 hp



# PETROL HIGH FLOW HYDROSTATIC PIPE BARRET TESTER

Engine - Drive: Petrol
Engine - Start: Electric
Pump - Speed: 550 RPM

#### **Range Review**

Part #	Туре	Pressur	eFlow	EnginePump - Type	Pump - Speed
210 APS41- GX200	High Flow	568 psi	41 L/mi	Petrol Diaphragn nHonda 6.5 hp Recoil	-
210 APS71- GX270	High Flow	568 psi	71 L/mi	Petrol Diaphragn nHonda 9.0 hp Recoil	n550 RPM
210 APS121- GX390	High Flow	568 psi		Petrol Diaphragn nHonda 13 hp Recoil	n550 RPM
210 APS149- GX630	High Flow	435 psi		Petrol Diaphragn nHonda 23 hp E Start	n550 RPM
210 APS41- KD225	High Flow	568 psi		Diesel Diaphragn nKohler 4.8 hp E Start	n550 RPM
210 APS71- KD440	High Flow	568 psi	71 L/mi	Diesel Diaphragn nKohler 10 hp E Start	n550 RPM
210 APS149- KD4252	High Flow	435 psi		Diesel Diaphragn nKohler 12 hp E Start	1550 RPM
210 APS145- D1000	High Flow	435 psi			n550 RPM
210 BAR2565G HJJ HTS	- High Pressur				



### PETROL HIGH FLOW HYDROSTATIC PIPE BARREN TESTER

210 BAR2565G- High 2,500 psi11 Petrol Plunger **HEJJ HTS** Pressure L/minHonda 6.5 hp E Start 210 BAR3513G- High 3,500 psi15 Petrol Plunger L/minHonda **HM HTS** Pressure 13 hp Recoil 210 BAR3513G- High 3,500 psi15 Petrol Plunger **HEM HTS** Pressure L/minHonda 13 hp E Start 210 BAR4023G- High 4,000 psi20 Petrol Plunger **HER HTS** Pressure L/minHonda 23 hp E Start 210 BAR5027G- High 5,000 psi21 Petrol Plunger **HER HTS** Pressure L/minHonda 27 hp E Start 210 BAR2048G- High 2,000 psi11 Diesel Plunger **KE HTS** Pressure L/minKohler 4.8 hp E Start 210 BAR4018G- High 4,000 psi15 Diesel Plunger **KER HTS** Pressure L/minKohler 18 hp E Start

