

# HIGH PRESSURE TRIPLEX PUMP - TW SERIES - SOLID, 30 MM SHAFT - COMET



SKU: 210 TW7050S

**24.9 L/min @ 5000 PSI**  
**1450 RPM**  
**21.3 HP, 20 KG**



## Features

- Brass Head
- Die-Cast Aluminum Alloy for Protection Against Corrosion
- Piston Guides are Heat Treated Stainless Steel
- Highly Efficient Stainless Steel Check Valves
- Solid Ceramic Plungers
- Brass Manifold: Forged for Maximum Strength and Longer Life up to 345 bar
- Solid Bronze Alloy Connection Rods
- High Quality Tapered Roller Bearings
- Large Oil Capacity Dissipates Heat and Improves Lubrication for Longer Life
- High Volume up to 53,5 l/min
- Long Life Seals
- Exclusive No-Oil-Leak System in the crankcase minimising wear of the piston oil seal (Patented)
- Exclusive Sealing System Between Crankcase And Pump Head that prevents dust and dirt getting inside where the pistons work but letting water out (Patented)
- Solid Shaft 24 or 30 mm for Belt Drive, Gearbox or Flex Couplers
- Standard versions with p.t.o on right hand side, left side on request.



## Specifications

- **Comet Model:** 6513 3100
- **Shaft:** Solid, 30 mm
- **Speed:** 1450 RPM
- **Flow:** 24.9 L/min - 6.6 GPM
- **Pressure:** 5000 PSI - 345 BAR - 34.5 Mpa
- **Power:** 21.3 HP - 15.9 kW
- **Weight:** 20 KG - 44 lbs
- **Inlet:** 1/2" BSP F
- **Outlet:** 3/8" BSP F



# HIGH PRESSURE TRIPLEX PUMP - TW SERIES - SOLID, 30 MM SHAFT - COMET



- **Head Material:** Brass
  - **Pump Type:** Triplex
- 

