HIGH PRESSURE TRIPLEX PUMP - RW SERIES - SOLID, 24 MM SHAFT - COMET



SKU: 210 RW3545S

12.4 L/min @ 4500 PSI 1450 RPM 9.8 HP, 11.5 KG

Features

- Brass Head
- Crankcase: Die-Cast Aluminum Alloy for Protection Against Corrosion
- Piston Guides are Heat Treated Stainless Steel
- Highly Efficient Stainless Steel Check Valves
- Solid Ceramic Plungers
- Brass Manifold: Forged for Maximum Strenght and Longer Life up to 310 bar
- One Piece, Solid Bronze Alloy Connection Rods
- High Quality Tapered Roller Bearings
- Large Oil Capacity Dissipates Heat and Improves lubrication for Longer Life
- Exclusive No-Oil-Leak System in the crankcase minimising wear of the piston oil seal (Patented)
- Exclusive Sealing System Between Crankcase And Pump Head that prevents dust and dirt getting inside where the pistons work but letting water out (Patented)
- Solid Shaft 24mm for Belt Drive, Gearbox or Flex Couplers
- · Nickel plated head available on request
- Standard versions with p.t.o on right hand side, left side on request.

Specifications

Comet Model: 6517 2300
Shaft: Solid, 24 mm
Speed: 1450 RPM

• Flow: 12.4 L/min - 3.3 GPM

• Pressure: 4500 PSI - 310 BAR - 31 Mpa

Power: 9.8 HP - 7.3 kWWeight: 11.5 KG - 25.3 lbs

• Inlet: 1/2" BSP F







HIGH PRESSURE TRIPLEX PUMP - RW SERIES - SOLID, 24 MM SHAFT - COMET



Outlet: 3/8" BSP FHead Material: BrassPump Type: Triplex

