

FLOW SWITCH (D01)



SKU: 145 28.0530.10

Flow rate 30 L/min - 8 USGpm

Temp 75°C - 165°F

Max Voltage 230 V

Flow Switch FL3 Delrin 3/8 BSPM

Electrical accessories: FL3 - Flow switch with probe

P/N	Shutter	Gauge bolt	Weight	Package Quantity	Prompt Delivery
28.0500.10	Delrin	-	288 gr - 10,16 oz	25	☐
28.0540.10	Brass	-	300 gr - 10,58 oz	25	☐
Brass piston covering					
28.0530.10	Delrin	1 x 1/4 Bsp F	308 gr - 10,86 oz	25	☐
With 1/4 Bsp F gauge port					
28.0535.00	Brass	1 x 1/4 Bsp F	318 gr - 11,22 oz	25	☐
With 1/4 Bsp F gauge port					

Specifications

- **Inlet:** 3/8 Bsp M
- **Outlet:** 3/8 Bsp M
- **Rated Pressure:** 250 Bar - 25 Mpa - 3650 Psi
- **Permissible Pressure:** 280 Bar - 28 Mpa - 4050 Psi
- **Rated Flow Rate:** 30 L/min - 8 USGpm
- **Level posit.*:** 3 L/min - 0,8 USGpm
- **Standing posit.*:** 3 L/min - 0,8 USGpm
- **Max. working. Temp:** 75°C - 165°F
- **Max. Voltage:** 230 V
- **Max. Curr. Strength:** 3 A
- **Max. switch capacity:** 60 VA
- **Electric cable:** 2x0,5 mmq.
- **Cable length:** 1250 mm - 49,2 in
- **Electrical insulation:** 55 IP



FLOW SWITCH (D01)

