## HIGH PRESSURE TRIPLEX PUMP - FWS2 EACH SERIES - SOLID, 24 MM SHAFT - COMET



SKU: 210 FWS24530S

17.5 L/min @ 3000 PSI 1750 RPM 10 HP, 8.8 KG

## **Features**

- Brass Head
- Reversible Crankcase for Right or left Hand Mounting
- Hardened Stainless Steel piston Guides Highly Efficient Stainless Steel Check Valves
- Solid Ceramic Plungers
- High & Low Pressure Seals: High Quality Buna-Textile Packings
- Additional Anti-Extrusion Ring under the Seal
- Solid Brass Manifolds
- Special Forged Brass Oversized Connecting Rods
- Die-Cast, Anodized Aluminum Crankcase
- Highly Quality Tapered Roller Bearings
- Optimal Oil Bath for High Speed Operation
- S 24mm Solid Shaft for Belt Drive, Gearbox or Flex Couplers
- · Nickel plated head available on request
- Standard versions with p.t.o on right hand side, left side on request.

## **Specifications**

• Comet Model: 6411 0300

• Shaft: Solid, 24 mm

• Speed: 1750 RPM

• Flow: 17.5 L/min - 4.6 GPM

• Pressure: 3000 PSI - 207 BAR - 20.7 Mpa

Power: 10 HP - 7.5 kW
Weight: 8.8 KG - 19.4 lbs
Inlet: 1/2" BSP Female

• Outlet: 3/8" BSP Female

Head Material: Brass

• Pump Type: Triplex







## HIGH PRESSURE TRIPLEX PUMP - FWS2 **SERIES - SOLID, 24 MM SHAFT - COMET**



