

HIGH PRESSURE TRIPLEX PUMP - FWS2 SERIES - SOLID, 24 MM SHAFT - COMET



SKU: 210 FWS24530S

17.5 L/min @ 3000 PSI
1750 RPM
10 HP, 8.8 KG



Features

- Brass Head
- Reversible Crankcase for Right or left Hand Mounting
- Hardened Stainless Steel piston Guides Highly Efficient
Stainless Steel Check Valves
- Solid Ceramic Plungers
- High & Low Pressure Seals: High Quality Buna-Textile
Packings
- Additional Anti-Extrusion Ring under the Seal
- Solid Brass Manifolds
- Special Forged Brass Oversized Connecting Rods
- Die-Cast, Anodized Aluminum Crankcase
- Highly Quality Tapered Roller Bearings
- Optimal Oil Bath for High Speed Operation
- S 24mm Solid Shaft for Belt Drive, Gearbox or Flex
Couplers
- Nickel plated head available on request
- Standard versions with p.t.o on right hand side, left side
on request.



Specifications

- **Comet Model:** 6411 0300
- **Shaft:** Solid, 24 mm
- **Speed:** 1750 RPM
- **Flow:** 17.5 L/min - 4.6 GPM
- **Pressure:** 3000 PSI - 207 BAR - 20.7 Mpa
- **Power:** 10 HP - 7.5 kW
- **Weight:** 8.8 KG - 19.4 lbs
- **Inlet:** 1/2" BSP Female
- **Outlet:** 3/8" BSP Female
- **Head Material:** Brass
- **Pump Type:** Triplex



HIGH PRESSURE TRIPLEX PUMP - FWS2 SERIES - SOLID, 24 MM SHAFT - COMET

