HIGH PRESSURE TRIPLEX PUMP - RWS SERIES - HOLLOW, 1 1/8" SHAFT -COMET



SKU: 210 RWS5530E

21.4 L/min @ 3000 PSI 1750 RPM 11.2 HP, Suits Electrical Engines

Features

- Brass Head
- Crankcase: Die-Cast Aluminum Alloy for Protection Against Corrosion
- Piston Guides are Heat Treated Stainless Steel
- Highly Efficient Stainless Steel Check Valves
- Solid Ceramic Plungers
- Brass Manifold: Forged for Maximum Strenght and Longer Life up to 276 bar
- One Piece, Solid Bronze Alloy Connection Rods
- High Quality Tapered Roller Bearings
- Large Oil Capacity Dissipates Heat and Improves lubrication for Longer Life
- Exclusive No-Oil-Leak System in the crankcase minimising wear of the piston oil seal (Patented)
- Exclusive Sealing System Between Crankcase And Pump Head that prevents dust and dirt getting inside where the pistons work but letting water out (Patented)
- 1" 1/8 HOLLOW SHAFT with flange for coupling to electric engines
- · Nickel plated head available on request
- Standard versions with p.t.o on right hand side, left side on request.

Specifications

Comet Model: 6518 0701
Shaft: Hollow, 1 1/8"
Speed: 1750 RPM

• Flow: 21.4 L/min - 5.7 GPM

• Pressure: 3000 PSI - 207 BAR - 20.7 Mpa

Power: 11.2 HP - 8.3 kW
Weight: 11.2 KG - 24.6 lbs

• Inlet: 1/2" BSP F







HIGH PRESSURE TRIPLEX PUMP - RWS SERIES - HOLLOW, 1 1/8" SHAFT -COMET



• Outlet: 3/8" BSP F

• Head Material: Brass

• Pump Type: Triplex

