

SKU: 125 85.402.106

**Capacity: 45 m of 3/8" Hose**  
**Perf: 5,075 PSI (Max.)**  
**In/Out: 3/8" F**

## Features

- Industrial A-Frame Crank Reel
- A new reel, offered as an option to 125 85.402.105 A Frame Style. This reel has inlet at the side, rather than through the drum. This prevents the retention of water in the drum that may cause rust
- A Frame style provides more support in mobile applications
- Universal 130 mm hole centre footprint
- High gloss powder-coated finish
- Extra heavy duty 6 point locking pin and adjustable rubber friction brake
- Dual heavy-duty sealed axle ball bearing with stainless steel hardware
- High-flow stainless steel swivel with Parker Viton O-Rings
- The reversible handle and swivel, let you switch sides for the best mounting option
- Hose guide to guard hose from reload damage (2100462)
- Optional 12-Volt power rewind kit. Includes mounting bracket, ring gear and hardware (103166)
- **HOSE NOT INCLUDED**

## Specifications

- **Capacity:** 45 m of 3/8" Hose
- **Max Pressure:** 5,075 PSI
- **Max Flow:** 80 L/min
- **Inlet Hose:** 3/8" F
- **Outlet Swivel:** 3/8" F
- **Max Temperature:** 150°C
- **Material:** Steel with Stainless Steel fittings
- **Dimensions:**
- **Weight:**
- **Brand:** GP



# HOSE REEL - CRANK - A FRAME

---

