

SKU: 220 SLR167/250-2200

Pressure - 3625 psi
Flow - 167 L/min
Speed - 2200 RPM



Features

- Pump body: spheroidal cast iron
- Head: spheroidal cast iron with chemical nickel plating
- Camshaft: steel
- Splash lubrication
- Shaft support bearings oversized for long duration
- Connecting rods: cast iron with thin-shell bearings
- Guiding piston: stainless steel
- Solid ceramic plungers
- Suction/delivery valves in stainless steel
- Seals: high dependability, V profile
- Versions in direct drive mount or with side gearbox available in 3 gear ratios and positionable on the right or left of the pump at 0° – 45° – 90° – 135° – 180° from the horizontal plane (see drawing)

Specifications

- **HPP Model** - SLR 167/250
- **HPP Code** - 6909 0036
- **Speed** - 2200 RPM
- **Flow** - 167 L/min
- **Pressure** - 3625 psi
- **Power** - 111 hp
- **Max Inlet Pressure** - 43.5 psi
- **Oil Capacity** - 8.98 L 80W 90
- **Oil Capacity with Gearbox** - 1500/1800 rpm 10.50 L – 2200 rpm, 11.47 L 80W 90
- **Weight** - 270 kg

Options

1. PULSE system on request
2. COOLER system (option)

