



SKU: 145 25.6000.10

Flow 100 L/min - 26,45 USGpm  
Stainless Steel 303  
NPT Nozzle Ports (Nozzles not Included)

Mosmatic Open Top Cleaning Head - Self-Propelling

These high quality, Italian made cleaning heads are the ideal choice for cleaning closed containers.

Specifications

- 1,015 PSI Rated Pressure
- 435 - 1,015 PSI Total Pressure Range
- 100 L/min Flow Rate Range
- 90°C Max Temperature Rating
- 360° Spray Coverage
- 183 mm ( ) Minimum Barrel Diameter
- 1-1/4" BSP Female Inlet Port
- (4) 1/4" NPT Nozzle Ports (Nozzles not Included)
- 4-5 Giri/min Rated RPM
- 10.2 kg Unit Weight
- 303 Stainless Construction

Range Review

Part Number	Flow	Nozzle Type	Min.overall Ø	Weight
145 25.6000.10	100 L/min	4 × 1/4 NPT	183 mm - 7,19"	10,200 gr / 360 oz
145 25.6000.15	130 L/min	4 × 1/4 NPT	183 mm - 7,19"	10,200 gr / 360 oz
145 25.6000.17	150 L/min	4 × 1/4 NPT	183 mm - 7,19"	10,200 gr / 360 oz
145 25.6000.20	180 L/min	4 × 1/4 NPT	183 mm - 7,19"	10,200 gr / 360 oz
145 25.6000.24	220 L/min	4 × 1/4 NPT	183 mm - 7,19"	10,200 gr / 360 oz
145 25.6000.30	300 L/min	4 × 1/4 NPT	183 mm - 7,19"	10,200 gr / 360 oz



# OPEN TOP CLEANING HEAD



## **\*Nozzles Not Included**

Once Cleaning Head is Selected, Fill Out Specifications Sheet and Submit to BAR for Confirmation.

---

