

HOT WATER PRESSURE CLEANER CABINET 2,200 PSI @ 21 L/MIN



SKU: 108 HOT150 21S

Sitemaster with Foamer Speed 1450 Rpm 230/400 V 50 Hz TRI

Sitemaster 150/21

Painted Steel Structure with Stainless Steel Door. Flame Control Photocell. Delayed Total Stop with Leakage Control. Automatic by Pass Valve. Safety Valve. Temperature Adjustment Thermostat (Flow Switch and Pressure Switch). High Efficient Stainless Steel Vertical Boiler. Ventilation by Independent Electric Motor. Water Level Control Float and Machine Stop in Case of Lack of Water. Double Flange Motor. Motor and Pump Connection with Elastic Coupling. High Pressure Chemical Suction. 24 V Low Tension Electrical Controls. Magnetothermic Overload Switch. Internal Acoustic and Thermic Lagging (anti Frost Protection). Lockable Electrical Controls.

Equipment:

STANDARD

- 10 M HP Hose with Quick Coupling
- 120 Cm Lance
- Professional gun
- Stainless Steel Water Nozzle

OPTIONAL

- Chimney Protection
- Pre-arrangement for Remote Control
- Sandblasting Head
- Rotating Nozzle
- Stainless Steel Cabinet
- Electrical Antiscale System
- Drain Pipe Kit











HOT WATER PRESSURE CLEANER CABINET 2,200 PSI @ 21 L/MIN



Performance:

- 2200 Psi @ 21 L/min
- Speed 1450 Rpm
- 230/400 V 50 Hz TRI
- Temperature 30-100°C

CARATTERISTICHE TECNICHE					TECHNICAL FEATURES				
	 BAR / PSI	 °C / °F	 MIN / °C MAX	 HP / KW / RPM		 KWATT	 CM	 KG	
SITEMASTER 100/12	100 - 1500	720 - 180	30 - 100	3,0 2,2 1450	230V 50Hz MONO	2,5	165x55x85	220	
SITEMASTER 150/15	150 - 2200	900 - 199	30 - 100	5,5 4,0 1450	230/400V 50Hz TRI	5,8	165x55x85	220	
SITEMASTER 150/21	150 - 2200	1800 - 474	30 - 100	7,5 5,5 1450	230/400V 50Hz TRI	5,8	165x55x85	220	
SITEMASTER 200/15	200 - 2900	900 - 199	30 - 100	7,5 5,5 1450	230/400V 50Hz TRI	5,8	165x55x85	220	
SITEMASTER 200/21	200 - 2900	1800 - 474	30 - 100	10 7,5 1450	230/400V 50Hz TRI	7,8	165x55x85	230	

