

# NOZZLE 5000@15-23 L/M (B1)



SKU: 165 Warthog WV 1/4 B

## Nozzle 5000 Psi 15-23 L/min Jet Angle Front 1 @ 15° Jet Angle Back 2@ 55°

### Warthog Nozzle WV 1/4"

The WV-1/4-LK uses StoneAge's flow-through technology and features a revolutionary high-speed rotating design with no high-pressure seals or bearings to service making it low maintenance. It cleans lines as small as 2" (51 mm) with long sweeping elbows.

The tool has a 1/4" NPT pipe thread inlet and can pass through long radius elbows in lines 2" (51 mm) and larger if a 1/4" NPT hose fitting is used.

### Features

- Rotational speed controlled by pressure/flow
- Excellent for navigating elbows
- Clears grease, fat, ice and fine roots

### Specifications

- **Nozzle Pressure:** 1200-5000 Psi
- **Flow:** 19-23 L/min
- **Jet Angle Front:** 1 @ 15°
- **Jet Angle Back:** 2@ 55°

*Note: No repair is available for WV series.*

**WARNING: Dismantling of Nozzle must be undertaken with WV181 and BA182 Change Out tools. Failure to do this will damage the nozzle head and void warranty**

Repairing your WV Nozzle:



### Recommended Accessories

- **Warthog Nozzle Repair Tool (B1)** 165 Warthog BA181
- **WV Head Removal Tool (A)** 165 Warthog BA182

